

SAFFTY DATA SHFFT

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830 - United Kingdom (UK)

Centrecoat MMA FG Colour Coat Base

1/8

Revision date 2019-10-29

Revision

4	1		о,	-	۱	ot.	ia	0	4ifi	er
	_	I . I	r	w	w		ю	en	ш	er

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use [SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC9a] Coatings and paints, thinners, paint removers; [PROC10] Roller application or brushing;

1.3. Details of the supplier of the safety data sheet

Company Promain UK Limited
Address C1 Pierson Court

Knowl Piece, Hitchin

Hertfordshire SG4 0TY

Web www.promain.co.uk

Telephone 01462 421333

Fax .

Email info@promain.co.uk

1.4. Emergency telephone number

Emergency telephone number | 01462 421333

8.30am - 5.30pm Mon - Thurs. 8.30am - 4.30pm Fri

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC	Flam. Liq. 2: H225; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335;
1272/2008	

2.2. Label elements

Hazard pictograms





Signal Word

Hazard Statement

Danger

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT SE 3: H335 - May cause respiratory irritation.

Precautionary Statement:

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Revision Revision date 2019-10-29

2.2. Label elements

P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting// equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 - IF ON SKIN: Wash with plenty of water/ .
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse
skin with water/shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 - Call a POISON CENTER/doctor/ /if you feel unwell.
P321 - Specific treatment (see on this label).
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

Precautionary Statement:

Precautionary Statement:

Storage

Response

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P370+P378 - In case of fire: Use to extinguish.

P405 - Store locked up.

Precautionary Statement:

Disposal

P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Methyl methacrylate	607-035-00-6	80-62-6	201-297-1	01-2119452498-28		Flam. Liq. 2: H225; STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317;
2-Ethylhexyl acrylate	607-107-00-7	103-11-7	203-080-7	01-2119453158-37		STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317;
N,N-bis-(2-hydroxypropyl) -p-toluidine		38668-48-3	254-075-1	01-2119980937-17		Acute Tox. 2: H300; Eye Irrit. 2: H319; Aquatic Chronic 3: H412;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.		
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing.		
	lenses, ii present and easy to do. Continue mising.		
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.		
Ingestion	DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water.		
4.2. Most important symptoms and effects, both acute and delayed			

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.
Eye contact	Irritating to eyes.
Skin contact	Irritating to skin.
Ingestion	Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation Seek medical attention.

Revision 1
Revision date 2019-10-29

		Revision date 2019-10-2				
4.3. Indication of any immed	liate medical attention and special treatment need	ded				
Eye contact						
Skin contact	Seek medical attention if irritation or symptoms persist.					
Ingestion	Seek medical attention.					
SECTION 5: Firefighting	measures					
5.1. Extinguishing media						
	Carbon oxides. Dry chemical. Foam. Do No	OT use water jet.				
5.2. Special hazards arising	from the substance or mixture					
	Highly flammable. Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.					
5.3. Advice for firefighters						
	Self-contained breathing apparatus. Wear	protective clothing.				
SECTION 6: Accidental r	release measures					
6.1. Personal precautions. p	rotective equipment and emergency procedures					
	Ensure adequate ventilation of the working	area. Wear suitable protective equipment. Eliminate all a safe area. Wear suitable respiratory equipment when				
6.2. Environmental precaution	ons					
	Do not allow product to enter drains. Preve	nt further spillage if safe.				
6.3. Methods and material fo	or containment and cleaning up					
		ep up. Transfer to suitable, labelled containers for th plenty of water. Use explosion proof equipment.				
6.4. Reference to other secti	ions					
	See section 8 for further information. See section 13 for further information.					
SECTION 7: Handling an	nd storage					
7.1. Precautions for safe har	ndling					
	· ·	dequate ventilation of the working area. Use explosion of ignition - No smoking. Vapours are heavier than air.				
7.2. Conditions for safe stora	age, including any incompatibilities					
	Keep in a cool, dry, well ventilated area. Ke containers. Store in original container.	eep containers tightly closed. Store in correctly labelled				
7.3. Specific end use(s)						
	See section 1.2 for further information.					
SECTION 8: Exposure or	ontrols/personal protection					
8.1. Control parameters	Shirolo/porconal protocolori					
8.1.1. Exposure Limit Values	B					
Methyl methacrylate	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m3: 208				
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m3: 416				
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -				
	inhalable dust: WEL 8-hr limit mg/m3 total -	inhalable dust: WEL 15 min limit mg/m3 total -				
	respirable dust:	respirable dust:				

Revision 1
Revision date 2019-10-29

8.2. Exposure controls







8.2.1. Appropriate engineering

controls

Wear chemical protective clothing.

8.2.2. Individual protection

measures

wear chemical protective clothing

Eye / face protection

Skin protection - Handprotection

Approved safety goggles.

Chemical resistant gloves (PVC). Butyl rubber gloves.

Ensure adequate ventilation of the working area.

Skin protection - Other

Wear suitable protective clothing.

Respiratory protection Wear suitable respiratory equipment when necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance | Liquid

Colour Various

....

Odour Strong/Characteristic

Odour threshold No data available

pH No data available

Melting point Not applicable.

Freezing Point -48 °C

Initial boiling point 100 °C

Flash point 10 °C

Evaporation rate Not applicable.

Flammability (solid, gas) No data available

Upper Explosive Limit 12.5 %

Lower Explosive Limit 2.1 %

Vapour pressure No data available

Vapour density No data available

Relative density 0.979 (H2O = 1 @ 20 °C)

Fat Solubility No data available

Partition coefficient No data available

Autoignition temperature 430 °C

Viscosity 200 mPas (Cone & Plate)

Explosive properties No data available

Oxidising properties No data available

Solubility | Slightly soluble in water

9.2. Other information

Conductivity No data available

Surface tension | No data available

Gas group No data available

Benzene Content 0 %

Lead content 0

VOC (Volatile organic | 0 g/l

compounds)

nt 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Revision 1
Revision date 2019-10-29

		Revision date 2019-10-29				
10.1. Reactivity						
	See section 10.2 for further information.					
10.2. Chemical stability	'					
	Stable under normal conditions.					
10.3. Possibility of hazardous re						
10.3. Possibility of flazardous re	1					
	Oxidising agents.					
10.4. Conditions to avoid	T					
	Heat, sparks and open flames.					
10.5. Incompatible materials						
	Alkalis. Oxidising agents. Peroxides. Reducing age	ents. Sulphur oxides.				
10.6. Hazardous decomposition	products					
	Will not decompose if stored and used as recomme	ended.				
SECTION 11: Toxicological	information					
11.1. Information on toxicological						
Acute toxicity	Oral Rat LD50 = >5,000mg/kg (Methyl Methacrylati	<u> </u>				
Skin corrosion/irritation	Irritating to skin.	e).				
Serious eye damage/irritation	Irritating to eyes.					
Respiratory or skin	May cause sensitisation by skin contact.					
sensitisation	,					
Germ cell mutagenicity	No mutagenic effects reported.					
Carcinogenicity	No carcinogenic effects reported.					
Reproductive toxicity	No observed effect level. No teratogenic effects reported.					
Aspiration hazard	No Significant Hazard.					
11.1.4. Toxicological Information	า					
2-Ethylhexyl acrylate	Oral Rat LD50: 4,435mg/kg	Dermal Rabbit LD50: >5,000mg/kg				
Methyl methacrylate	Dermal Rat LD50: >5,000mg/kg	Oral Rat LD50: >2,000mg/kg				
	Dermal Rabbit LD50: >5,000mg/kg	Inhalation Rat LC50/4 h: 29.8mg/kg				
N,N-bis-(2-hydroxypropyl) -p-toluidine	Oral Rat LD50: 172mg/kg					
	,					
SECTION 12: Ecological info	ormation					
12.1. Toxicity						
Methyl methacrylate	Daphnia EC50/48h: 69.0000 mg/l	Fish LC50/96h: 79.0000 mg/l				
12.2. Persistence and degradab	sility					
12.2. Fersisterice and degradat	1					
40.0 P' 1.0' 1.0' 1	Readily biodegradable. OECD 301C, 14D.					
12.3. Bioaccumulative potential						
	No observed effect level.					
Partition coefficient						
	Centrecoat MMA FG Colour Coat No data available	e				
	Base					
12.4. Mobility in soil						
	Slightly soluble in water.					
	· · · · ·					

Revision 1
Revision date 2019-10-29

12.5. Results of PBT and vPvB assessment PBT no vPvB no 12.6. Other adverse effects No data is available on this product. SECTION 13: Disposal considerations General information 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances. Disposal methods The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact sith soil, waterways, drains and sewers. Disposal of packaging Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. SECTION 14: Transport information Hazard pictograms 14.1. UN number UN1866 14.2. UN proper shipping name RESIN SOLUTION ((Methyl Methacrylate)) 14.3. Transport hazard class(es) ADR/RID 3 Subsidiary risk **IMDG** 3 Subsidiary risk **IATA** 3 Subsidiary risk 14.4. Packing group Ш Packing group 14.5. Environmental hazards No **Environmental hazards** Marine pollutant No 14.6. Special precautions for user Not applicable.

Revision 1
Revision date 2019-10-29

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code		
	Not applicable.	
ADR/RID		
Hazard ID	33	
Tunnel Category	(D/E)	
IMDG		
EmS Code	F-E S-E	
IATA		
Packing Instruction (Cargo)	364	
Maximum quantity	60 L	
Packing Instruction (Passenger)	353	
Maximum quantity	5 L	
Further information		
	The product is not classified as dangerous for carriage.	

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

15.2. Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas:.
	4 - Eye contact.
Text of Hazard Statements in	Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Section 3	Skin Irrit. 2: H315 - Causes skin irritation.
	Skin Sens. 1: H317 - May cause an allergic skin reaction.
	STOT SE 3: H335 - May cause respiratory irritation.
	Acute Tox. 2: H300 - Fatal if swallowed.
	Eye Irrit. 2: H319 - Causes serious eye irritation.
	Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Maximum content of VOC	0 g/l.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in

Revision 1
Revision date 2019-10-29

Further information

combination with any other materials or in any other process.