



TECHNICAL DATA SHEET

KEIM BLOCKWEISS

1. PRODUCT DESCRIPTION

KEIM Blockweiss is a white pigmented water-based stain blocker priming coat.

2. FIELD OF APPLICATION

KEIM Blockweiss is used to prime interior surfaces which have a staining/bleeding tendency. KEIM Blockweiss is preferably used to isolate and block the bleeding of marks and stains from water, oil, tar, soot, smoke or coloured pen. The substrate must be sound, dry and clean before application.

3. PRODUCT PROPERTIES

- Highly isolating
- Low-odour
- Aqueous
- Pigmented, very good hiding power

Material characteristics

Specific weight: approx. 1.30 g/cm³

Solids content: approx. 55%

Colour shades

White

4. APPLICATION INSTRUCTIONS

Substrate preparation and application

KEIM Blockweiss is applied to interior surfaces with problematic stains and bleedings. Application is ideally done on visually connected areas in order to achieve homogeneous results.

A one-coat primer coat application may be sufficient. In case of intensive stains two up to three applications are recommended.

A drying time of at least 12 hours between the coats is required. A drying time of 24 hours is necessary prior to subsequent coating with KEIM

interior paints. The application is to be done in sections.

Stir material well before application. Do not apply on distemper paints. Do not mix with other paints or tinting pastes. Dilution with water will impair the isolating properties.

Application conditions

Ambient and substrate temperature above 5°C and below 30°C. Do not apply in direct sunlight or onto sun-heated surfaces.

Consumption

Approx. 15 lt/m² for one coat

The stated consumption values are for a smooth surface and given for guidance and depend on the nature of the substrate and the application method. Exact consumption values can only be determined by trials on the substrate.

5. PACKAGING

2.5 lt or 12.5 lt containers

6. STORAGE

Shelf life is approx. 12 months if kept dry, cool, but frost-free in tightly closed containers. Protect from moisture.

7. DISPOSAL

EC Waste Code No. 08 01 12.

After contact with water and after hardening the product can be disposed of as building rubble.

8. SAFETY INSTRUCTIONS

GISBAU Product Code/ GISCODE: M-GP 01

Provide appropriate protection for surfaces which are not to be coated (e.g. glass, natural stone, ceramics, wood etc.). Any splashes on surrounding surfaces or traffic areas must be rinsed off immediately with plenty of water.

Provide constantly good ventilation during application and drying. Protect the eyes and skin from splashes. Do not eat, drink or smoke during application. Keep out of reach of children.

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release those purchasing and applying our products from the duty of establishing for themselves, with due care, the suitability of our products for the intended application. Standard building industry practices must be complied with. We retain the right to make modifications to improve the products or their application. This edition supersedes all earlier editions.

