

Page 1 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**beko MS-Flex farbig**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Seam sealant

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

beko GmbH  
Rappenfeldstr. 5  
DE-86653 Monheim  
Tel: +49 (0) 90 91 / 9 08 98-0  
Fax: +49 (0) 90 91 / 9 08 98-29  
info@beko-group.com  
www.beko-group.com

Qualified person's e-mail address: info@beko-group.com

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

Poison Control Center Mainz - 24 hour emergency service – phone: +49 (0) 6131/19240

**Telephone number of the company in case of emergencies:**

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

#### 2.2 Label elements

**Labeling according to Regulation (EC) 1272/2008 (CLP)**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

EUH208-Contains N-(3-(trimethoxysilyl)propyl)ethylenediamine, Trimethoxyvinylsilane. May produce an allergic reaction.  
EUH210-Safety data sheet available on request.  
EUH212-Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).  
The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).  
The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

3-(trimethoxysilyl)propylamine	
Registration number (REACH)	01-2119510159-45-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	237-511-5
CAS	13822-56-5
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Irrit. 2, H315 Eye Dam. 1, H318

Trimethoxyvinylsilane	
Registration number (REACH)	01-2119513215-52-XXXX
Index	014-049-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	220-449-8
CAS	2768-02-7
content %	0,1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Sens. 1B, H317

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)	
Registration number (REACH)	01-2119489379-17-XXXX
Index	022-006-002
EINECS, ELINCS, NLP, REACH-IT List-No.	236-675-5
CAS	13463-67-7
content %	0,01-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Carc. 2, H351 (as inhalation)

N-(3-(trimethoxysilyl)propyl)ethylenediamine	
Registration number (REACH)	01-2119970215-39-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	217-164-6
CAS	1760-24-3
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT SE 3, H335
Specific Concentration Limits and ATE	ATE (as inhalation, Vapours): 12,6 mg/l/4h

Page 3 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.  
For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
The substances named in this section are given with their actual, appropriate classification!  
For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
Never pour anything into the mouth of an unconscious person!

#### Inhalation

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Wipe off residual product carefully with a soft, dry cloth.  
Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.  
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.  
Do not induce vomiting - give copious water to drink. Consult doctor immediately.  
Upon contact with stomach acid development of:  
Methanol

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes  
Skin irritation possible with prolonged contact.  
Development of:

Methanol

The following applies to this substance:

Product results in a poisonous effect.

Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Adapt to the nature and extent of fire.  
Water jet spray / alcohol resistant foam / CO<sub>2</sub> / dry extinguisher.

#### Unsuitable extinguishing media

None known

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon  
Oxides of nitrogen

Methanol  
Formaldehyde  
Toxic gases

### 5.3 Advice for firefighters

For personal protective equipment see Section 8.  
In case of fire and/or explosion do not breathe fumes.

Page 4 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

Protective respirator with independent air supply.  
According to size of fire  
Full protection, if necessary.  
Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.  
Ensure sufficient ventilation, remove sources of ignition.  
Avoid dust formation with solid or powder products.  
Leave the danger zone if possible, use existing emergency plans if necessary.  
Ensure sufficient supply of air.  
Avoid contact with eyes or skin.  
If applicable, caution - risk of slipping.

#### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

### 6.2 Environmental precautions

If leakage occurs, dam up.  
Resolve leaks if this possible without risk.  
Prevent from entering drainage system.  
Prevent surface and ground-water infiltration, as well as ground penetration.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Or:

Pick up mechanically and dispose of according to Section 13.  
Flush residue using copious water.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.  
Avoid contact with eyes.  
Avoid long lasting or intensive contact with skin.  
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
Observe directions on label and instructions for use.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.  
Store product closed and only in original packing.  
Store in a well ventilated place.  
Store in a dry place.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

## 8.1 Control parameters

The methanol listed below can arise upon contact with water.

Chemical Name	Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)		Content %:0,01- <2,5
WEL-TWA: 10 mg/m3 (total inhalable dust), 4 mg/m3 (respirable dust)	WEL-STEL: ---	---	
Monitoring procedures: ---			
BMGV: ---		Other information: ---	
Chemical Name	Calcium carbonate		Content %:
WEL-TWA: 4 mg/m3 (respirable dust), 10 mg/m3 (total inhalable dust)	WEL-STEL: ---	---	
Monitoring procedures: ---			
BMGV: ---		Other information: ---	
Chemical Name	Methanol		Content %:
WEL-TWA: 200 ppm (266 mg/m3) (WEL), 200 ppm (260 mg/m3) (EU)	WEL-STEL: 250 ppm (333 mg/m3) (WEL)	---	
Monitoring procedures: <ul style="list-style-type: none"> <li>- Draeger - Alcohol 25/a Methanol (81 01 631)</li> <li>- Compur - KITA-119 SA (549 640)</li> <li>- Compur - KITA-119 U (549 657)</li> <li>- DFG Meth. Nr. 6 (D) (Lösungsmittelgemische 6), DFG (E) (Solvent mixtures 6) - 2013, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 65-1 (2004)</li> <li>- NIOSH 2000 (METHANOL) - 1998</li> <li>- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996</li> <li>- NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EXTRACTIVE FTIR SPECTROMETRY) - 2016</li> <li>- Draeger - Alcohol 100/a (CH 29 701)</li> </ul>			
BMGV: ---		Other information: Sk (WEL, EU)	

Trimethoxyvinylsilane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,4	mg/l	Für entsprechendes Silantriol (Hydrolyseprodukt) ermittelt.
	Environment - marine		PNEC	0,04	mg/l	Für entsprechendes Silantriol (Hydrolyseprodukt) ermittelt.
	Environment - water, sporadic (intermittent) release		PNEC	2,4	mg/l	Für entsprechendes Silantriol (Hydrolyseprodukt) ermittelt.

GB

Page 6 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

	Environment - sewage treatment plant		PNEC	6,6	mg/l	Für entsprechendes Silantriol (Hydrolysp-Produkt) ermittelt.
	Environment - sediment, freshwater		PNEC	1,5	mg/kg dw	Für entsprechendes Silantriol (Hydrolysp-Produkt) ermittelt.
	Environment - sediment, marine		PNEC	0,15	mg/kg dw	Für entsprechendes Silantriol (Hydrolysp-Produkt) ermittelt.
	Environment - soil		PNEC	0,06	mg/kg dw	Für entsprechendes Silantriol (Hydrolysp-Produkt) ermittelt.
Consumer	Human - dermal	Short term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,7	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	93,4	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,2	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,6	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	4,9	mg/m <sup>3</sup>	

**Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm)**

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,184	mg/l	
	Environment - marine		PNEC	0,0184	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,193	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, freshwater		PNEC	1000	mg/kg dw	
	Environment - sediment, marine		PNEC	100	mg/kg dw	
	Environment - soil		PNEC	100	mg/kg dw	

GB

Page 7 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

	Environment - oral (animal feed)		PNEC	1667	mg/kg feed	
Consumer	Human - oral	Long term, systemic effects	DNEL	700	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

### 3-(trimethoxysilyl)propylamine

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,33	mg/l	
	Environment - marine		PNEC	0,033	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	3,3	mg/l	
	Environment - sediment, freshwater		PNEC	1,2	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,12	mg/kg dry weight	
	Environment - soil		PNEC	0,045	mg/kg dry weight	
	Environment - sewage treatment plant		PNEC	0,81	mg/l	
	Environment - oral (animal feed)		PNEC	11,1	mg/kg	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	17,4	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	5	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,7	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,5	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	5	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	17,4	mg/m3	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	8,3	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	7,1	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg	

### N-(3-(trimethoxysilyl)propyl)ethylenediamine

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,062	mg/l	
	Environment - marine		PNEC	0,0062	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,62	mg/l	
	Environment - sediment, freshwater		PNEC	0,05	mg/kg wet weight	
	Environment - sediment, marine		PNEC	0,005	mg/kg wet weight	

GB

Page 8 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

	Environment - sewage treatment plant		PNEC	25	mg/l	
	Environment - soil		PNEC	0,009	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	2,5	mg/kg	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	50	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,1	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	4	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	2,5	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	8,7	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	2,5	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	35,5	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	5	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,6	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	260	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	5,36	mg/m3	

<b>Calcium carbonate</b>						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	6,1	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,06	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	6,1	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4,26	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	

<b>Methanol</b>						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	154	mg/l	
	Environment - marine		PNEC	15,4	mg/l	
	Environment - sediment, freshwater		PNEC	570,4	mg/kg	
	Environment - sediment, marine		PNEC	57,04	mg/kg	
	Environment - soil		PNEC	23,5	mg/kg	



Page 9 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

	Environment - water, sporadic (intermittent) release		PNEC	1540	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - inhalation	Long term, local effects	DNEL	26	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	26	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	4	mg/kg body weight/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	26	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	4	mg/kg body weight/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	4	mg/kg body weight/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	26	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	4	mg/kg body weight/day	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	20	mg/kg body weight/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	130	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	130	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	20	mg/kg body weight/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	130	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	130	mg/m3	

Ⓒ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.  
(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
Applies only if maximum permissible exposure values are listed here.

GB

Page 10 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
These are specified by e.g. EN 14042.  
EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
With danger of contact with eyes.  
Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
Chemical resistant protective gloves (EN ISO 374).  
If applicable  
Protective gloves made of butyl (EN ISO 374).  
Protective nitrile gloves (EN ISO 374).  
Protective gloves made of fluorocarbon rubber (EN ISO 374).  
Protective gloves made of vinyl (EN ISO 374).  
Permeation time (penetration time) in minutes:  
>480  
Minimum layer thickness in mm:  
>0,1  
Protective hand cream recommended.  
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:  
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
Normally not necessary.

Thermal hazards:  
Not applicable

Additional information on hand protection - No tests have been performed.  
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
Selection of materials derived from glove manufacturer's indications.  
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Paste, solid.
Colour:	According to specification
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	There is no information available on this parameter.

Page 11 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

Lower explosion limit:	Does not apply to solids.
Upper explosion limit:	Does not apply to solids.
Flash point:	Does not apply to solids.
Auto-ignition temperature:	Does not apply to solids.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	Does not apply to solids.
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	1,57 g/cm <sup>3</sup>
Relative vapour density:	Does not apply to solids.

## 9.2 Other information

Explosives:	Product is not explosive.
Oxidizing solids:	No

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

Strong heat

Protect from humidity.

Product may hydrolyse.

### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

### 10.6 Hazardous decomposition products

See also section 5.2

On contact with moist air:

Methanol

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

#### beko MS-Flex farbig

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Dust
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:					Expert Judgement	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:						n.d.a.

GB

Page 12 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
MS-Flex Polymer

Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

<b>3-(trimethoxysilyl)propylamine</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	3030	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	> 10000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion Chinese hamster
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	200	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Target organ(s): liver, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	LOAEL	600	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Target organ(s): liver, Analogous conclusion

<b>Trimethoxyvinylsilane</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	7120	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	3200	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	16,8	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Acute toxicity, by inhalation:	LD50	2773	ppm/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant

GB

Page 13 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Skin Sens. 1B
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative Chinese hamster
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Rat	OECD 489 (In Vivo Mammalian Alkaline Comet Assay)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:	NOAEL	1000	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEL	>= 75	mg/kg	Rabbit	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	0,58	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Vapours
Symptoms:						drowsiness, dizziness, nausea, abdominal pain, breathing difficulties, visual disturbances
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	62,5	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	Target organ(s): bladder

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LD50	>6,8	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant

GB

Page 14 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Mechanical irritation possible.
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitizing
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	No indications of such an effect.
Specific target organ toxicity - single exposure (STOT-SE):						Not irritant (respiratory tract).
Symptoms:						mucous membrane irritation, coughing, respiratory distress, drying of the skin.
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	3500	mg/kg/d	Rat		90d
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	10	mg/m <sup>3</sup>	Rat		90d

<b>N-(3-(trimethoxysilyl)propyl)ethylenediamine</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	2413	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	> 2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	1,49-2,44	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Skin Sens. 1B

GB

Page 15 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Skin Sens. 1B
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative Chinese hamster
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEL	>=500	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	
Reproductive toxicity (Effects on fertility):	NOAEL	>=500	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	>= 500	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	0,015	mg/l/6h/d	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	

<b>Calcium carbonate</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixed Dose Procedure)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative

GB

Page 16 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity:	NOEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development Tox. Screening Test)	
Specific target organ toxicity - single exposure (STOT-SE):						No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):						No indications of such an effect.
Aspiration hazard:						No
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	0,212	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	

<b>Methanol</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	ATE	300	mg/kg	Human being		Experiences on persons.
Acute toxicity, by dermal route:	LD50	17100	mg/kg	Rabbit		Does not conform with EU classification.
Acute toxicity, by inhalation:	LC50	85	mg/l/4h	Rat		Not relevant for classification., Vapours
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative



GB

Page 17 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

Carcinogenicity:				Mouse	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	1,3	mg/l	Mouse	OECD 416 (Two-generation Reproduction Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	0,13	mg/l	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	
Symptoms:						abdominal pain, vomiting, headaches, gastrointestinal disturbances, drowsiness, visual disturbances, watering eyes, nausea, mental confusion, intoxication, dizziness

## 11.2. Information on other hazards

beko MS-Flex farbig						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

beko MS-Flex farbig							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.

GB

Page 18 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							DOC-elimination degree (complexing organic substance) $\geq$ 80%/28d: n.a.

<b>3-(trimethoxysilyl)propylamine</b>							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	> 934	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	331	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	> 1000	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:	DOC	28d	67	%		Regulation (EC) 440/2008 C.4-A (DETERMINATION OF 'READY' BIODEGRADABILITY - DOC DIELAWAY TEST)	Not readily biodegradable (Analogous conclusion)
12.3. Bioaccumulative potential: QSAR	Log Kow		0,2				Not to be expected 20 °C
12.4. Mobility in soil:							Slight
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	6h	13	mg/l	Pseudomonas fluorescens		Analogous conclusion
Toxicity to bacteria:	EC50		3400	mg/l	activated sludge		

<b>Trimethoxyvinylsilane</b>							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	191	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	168,7	mg/l	Daphnia magna	Regulation (EC) 440/2008 C.2 (DAPHNIA SP. ACUTE IMMOBILISATION TEST)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	28	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	





GB

Page 21 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to bacteria:	NOEC/NOEL	3h	1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Glycine max
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Lycopersicon esculentum
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Avena sativa
Other organisms:	NOEC/NOEL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Glycine max
Other organisms:	NOEC/NOEL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Lycopersicon esculentum
Other organisms:	NOEC/NOEL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Avena sativa
Other organisms:	EC50	14d	>1000	mg/kg dw	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	
Other organisms:	NOEC/NOEL	14d	1000	mg/kg dw	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	
Other organisms:	EC50	28d	>1000	mg/kg dw		OECD 216 (Soil Microorganisms - Nitrogen Transformation Test)	
Other organisms:	NOEC/NOEL	28d	1000	mg/kg dw		OECD 216 (Soil Microorganisms - Nitrogen Transformation Test)	

GB

Page 22 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

Water solubility:			0,0166	g/l		OECD 105 (Water Solubility)	20°C
-------------------	--	--	--------	-----	--	--------------------------------	------

<b>Methanol</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	15400	mg/l	Lepomis macrochirus		EPA-660/3-75-009
12.1. Toxicity to daphnia:	EC50	96h	18260	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	96h	22000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	99	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		28400		Chlorella vulgaris		Not to be expected
Toxicity to bacteria:	IC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:	Log Pow		-0,77				
Other information:	DOC		<70	%			
Other information:	BOD		>60	%			

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

Hardened product:

E.g. dispose at suitable refuse site.

#### For contaminated packing material

Pay attention to local and national official regulations.

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

Empty container completely.

Untampered packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

## SECTION 14: Transport information

### General statements

14.1. UN number or ID number: n.a.

### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

n.a.

14.4. Packing group:

n.a.

Classification code:

n.a.

LQ:

n.a.

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

n.a.

14.4. Packing group:

n.a.

Marine Pollutant:

n.a.

14.5. Environmental hazards:

Not applicable

### Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

n.a.

14.4. Packing group:

n.a.

14.5. Environmental hazards:

Not applicable

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

General hygiene measures for the handling of chemicals are applicable.

Regulation (EU) No 649/2012 'concerning the export and import of hazardous chemicals' must be adhered to, as the product contains a substance that falls within the scope of this Regulation.

Directive 2010/75/EU (VOC):

0 %

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections:

15

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.

H351 Suspected of causing cancer by inhalation.

H317 May cause an allergic skin reaction.

H315 Causes skin irritation.

GB

Page 24 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

H318 Causes serious eye damage.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.

Skin Irrit. — Skin irritation  
Eye Dam. — Serious eye damage  
Flam. Liq. — Flammable liquid  
Acute Tox. — Acute toxicity - inhalation  
Skin Sens. — Skin sensitization  
Carc. — Carcinogenicity  
STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.  
Guidelines for the preparation of safety data sheets as amended (ECHA).  
Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).  
Safety data sheets for the constituent substances.  
ECHA Homepage - Information about chemicals.  
GESTIS Substance Database (Germany).  
German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).  
EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.  
National Lists of Occupational Exposure Limits for each country as amended.  
Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to  
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
AOX Adsorbable organic halogen compounds  
approx. approximately  
Art., Art. no. Article number  
ASTM ASTM International (American Society for Testing and Materials)  
ATE Acute Toxicity Estimate  
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
BCF Bioconcentration factor  
BSEF The International Bromine Council  
bw body weight  
CAS Chemical Abstracts Service  
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
CMR carcinogenic, mutagenic, reproductive toxic  
DMEL Derived Minimum Effect Level  
DNEL Derived No Effect Level  
DOC Dissolved organic carbon  
dw dry weight  
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)  
EC European Community  
ECHA European Chemicals Agency  
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect  
EEC European Economic Community  
EINECS European Inventory of Existing Commercial Chemical Substances  
ELINCS European List of Notified Chemical Substances  
EN European Norms  
EPA United States Environmental Protection Agency (United States of America)  
ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)  
etc. et cetera



GB

Page 25 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.02.2022 / 0006  
Replacing version dated / version: 01.11.2021 / 0005  
Valid from: 08.02.2022  
PDF print date: 08.02.2022  
beko MS-Flex farbig

EU European Union  
EVAL Ethylene-vinyl alcohol copolymer  
Fax. Fax number  
gen. general  
GHS Globally Harmonized System of Classification and Labelling of Chemicals  
GWP Global warming potential  
Koc Adsorption coefficient of organic carbon in the soil  
Kow octanol-water partition coefficient  
IARC International Agency for Research on Cancer  
IATA International Air Transport Association  
IBC (Code) International Bulk Chemical (Code)  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCLID International Uniform Chemical Information Database  
IUPAC International Union for Pure Applied Chemistry  
LC50 Lethal Concentration to 50 % of a test population  
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)  
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil  
Log Kow, Log Pow Logarithm of octanol-water partition coefficient  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
NIOSH National Institute for Occupational Safety and Health (USA)  
NLP No-longer-Polymer  
NOEC, NOEL No Observed Effect Concentration/Level  
OECD Organisation for Economic Co-operation and Development  
org. organic  
OSHA Occupational Safety and Health Administration (USA)  
PBT persistent, bioaccumulative and toxic  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
ppm parts per million  
PVC Polyvinylchloride  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SVHC Substances of Very High Concern  
Tel. Telephone  
TOC Total organic carbon  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.