



## QP Cat

Accelerator in the Remmers QP System

Availability	
Quantity per pallet	2000
<b>Packaging unit</b>	<b>0,1 kg</b>
Type of container	Can
Container code	81
<b>Art. no.</b>	
6898	■

**Application rate** See application examples

**Range of use** ■ Accelerator in the Remmers QP System

**Property profile** ■ Accelerates full hardening

**Possible system products** > [QP 100 \(6890\)](#)  
> [QP Color \(6895\)](#)

**Production of the mixture** ■ **Mixing**  
Add the entire quantity of the hardener (component B) to the base compound (component A).  
Then add component C (QP Cat) together with another container unit of QP Cat as accelerator.  
Mix thoroughly with a slow-speed electric mixer (approx. 300 - 400 rpm).  
Mix for at least 3 minutes.  
Insufficient mixing is indicated by streaks forming.

**Directions** For professional users only!

■ **Conditions for use**  
See the Technical Data Sheet for the binder being used.

■ **Working time (+20 °C)**



---

With addition of 0.1 kg QP Cat per container unit

approx. 20 min. at +20 °C  
approx. 30 min. at +10 °C  
approx. 60 min. at +0 °C

■ **Drying time (+20 °C)**

With addition of 0.1 kg QP Cat per container unit

approx. 60 min. at +20 °C  
approx. 130 min. at +10 °C  
approx. 270 min. at +0 °C

The times given are reduced at higher temperatures and increased at lower temperatures, in particular in combination with high humidity.

---

**Notes**

Unless otherwise specified, all of the values and application rates given above have been determined under laboratory conditions (20 °C) using standard colours. Slight deviations from these values may arise if the product is worked with on site.

Remmers QP Cat may be used as an accelerator for products in the Remmers QP system only.

Using an accelerator with products in the Remmers QP system may alter the properties (e.g. crack bridging, impact strength, processing time, colour and UV resistance) compared to the use of the products without an accelerator.

On continuous surfaces use only material with the same proportion of Remmers QP Cat in order to avoid slight differences in colour.

Use sufficiently experienced personnel to ensure that surfaces are as even as possible.

Further notes on working, system construction and maintenance of the listed products can be found in the latest Technical Data Sheets and the Remmers system recommendations.

---


**Tools / Cleaning**

See the Technical Data Sheet for the binder being used.

---

**Storage / Shelf life**

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.



---

**Safety data / Regulations**

For professional users only!

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

---

**Disposal**

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.



Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.