

Torstrip ABS water based paint stripper

SS4300006

intended uses

An advanced high performance water based stripping system. Specifically developed for the removal of multi-layers of both conventional and two-component paint finishes from ceilings and soffits, where the use of conventional stripping systems may not be appropriate.

product description

A blend of Benzyl Alcohol, surfactants and evaporation retardants.

product information

Product reference	SS4300006
Theoretical coverage	Up to 4 square metres per litre per coat
Practical coverage	Can vary, depends on number of paint coats, type of material, overall film thickness, substrate type, number of removals necessary, etc.
Appearance/Colour range	White / Milky
VOC content	0 grams/litre

application details

Method of Application See detailed Torstrip ABS Application Guidelines.

storage and handling

Storage	Store in a safe place out of the reach of children
Pack Size	25 litre drum, filled to 20kg
Flash point	Not classified as flammable
Product weight	1.15 kilogram/litre
Shelf life	1 year

surface preparation

Ensure surfaces to be stripped are dry. Waxy or extremely greasy surfaces should be thoroughly cleaned prior to stripping.

Adjacent surfaces which are not to be stripped should be suitably masked and protected, preferably with polypropylene sheeting.

limitations

Use as supplied. Do not dilute or add other products.

The area to be treated should not be allowed to dry out during treatment.

If scraping is attempted too early the stripper will not have had sufficient time to penetrate the layers and removal will be restricted.

safety precautions

A copy of the appropriate Health & Safety Data Sheet should be consulted prior to using the product. This can be faxed if urgently required.

Minimum precautions for all paints:

1. Avoid prolonged skin and eye contact i.e. wear suitable protective gloves, overalls, goggles, etc.
2. Ensure good ventilation, mechanical ventilation is not required.
3. Store and use away from heat and flame.
4. Do not eat or smoke in the vicinity of work.
5. Wash hands before eating.
6. Refer to supply container for additional warning labels.

Definitions

Tolerances

All information quoted in this data sheet is subject to normal manufacturing tolerances.

Practical coverage

Practical coverage can vary considerably depending on method of application, surface roughness, weather conditions and complexity of the structure.

Pot Life

Applies only to two pack products and refers to the time the mixture remains usable.

VOC

Volatile organic compounds

dft

Dry film thickness

wft

Wet film thickness

Disclaimer

The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Tor Coatings be liable for consequential or incidental damages.

This document will normally be updated at least every two years. It is the users responsibility to ensure that they have the current copy.

Updated: September 2013

SS4300006