

# PAINTS LTD

## TECHNICAL DATA SHEET

### BF011 Blackfriar Timba Dura.

Revision date: 08/08/2008
---------------------------------

<p><b><u>Product Information</u></b></p> <p><b><u>Description</u></b> A timber protector based on natural ingredients including beeswax and linseed oil.</p> <p><b><u>Usage/purpose</u></b> For exterior timber (ideal for cladding, fences, sheds, etc.). Not suitable for interior use.</p> <p><b><u>Characteristics</u></b> A highly structured 'woodstain' based on the Madison formulation. Stains, protects and finishes all in one.</p> <p><b><u>Finish</u></b> Slight sheen</p> <p><b><u>Colour(s)</u></b> Cedar.</p> <p><b><u>Packaging</u></b> 1litre, 2.5litre and 5 litre. Larger sizes may be available on request dependant on volume required</p> <p><b><u>Disclaimer;</u></b> The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.</p>	<p><b><u>Technical Spec</u></b></p> <p><b><u>Composition</u></b> A blend of natural ingredients including Beeswax, Linseed oil and permanent earth pigments.</p> <p><b><u>Properties</u></b> VOC Content: 200-207 g/litre.</p> <p><b><u>Performance</u></b> Typical recoating schedule of 5 years. A durable, flexible, water repellent, microporous coating. Resists flaking and peeling.</p> <p><b><u>Surface Preparation</u></b> Ensure the substrate to be coated is sound and free from any surface contaminant likely to give adhesion problems (wax, grease, polish etc). Wipe down surface of wood with White spirit to remove superficial wood oils. Allow to dry fully.</p> <p><b><u>Application Method</u></b> Short bristled brush or Rag. Three coats recommended. Cedar wood should require only two coats due to the resilience of the wood. Apply thinly.</p> <p><b><u>Recommended Spreading Rate</u></b> 12-15m<sup>2</sup>/ltr depending on the porosity of the wood.</p>	<p><b><u>Thinning</u></b> Do not thin.</p> <p><b><u>Drying Time</u></b> Touch dry in 2-4 hours Recoat after 16 hours under normal conditions (20°C 50% r/h).</p> <p><b><u>Cleaning</u></b> Clean application equipment or spills with white spirit or Blackfriar Brush Cleaner</p> <p><b><u>Limitations</u></b> Only suitable for new, bare wood or weathered Timba Dura. Not recommended for use on horizontal surfaces, joinery (windows, doors), garden furniture. Rags used with this material are combustible. Destroy all rags after use by burning outside.</p> <p><b><u>Environmental Info.</u></b> Dangerous for the environment</p>
		<p><b>Paint Product</b> UN No. 1263.</p>